

# CERETAN<sup>®</sup> MA 7019

## TECHNICAL INFORMATION

**Chemical description:** Micronized ethylene-bis-stearamide-wax [EBS]

**Applications:** **Paints and coatings**, e.g. powder-, industrial-, furniture- and parquet coatings

**Properties:**

- Lubricant / demoulding agent for engineering plastic (PA, PC, PET)
- Matting agent
- Degassing agent for powder coatings
- Improved slip, abrasion resistance and antiblocking properties

**Advantages:**

- Spherical particle shape made by unique spraying technology
- Specified maximum particle size (D99 value) and narrow and uniform particle size distribution
- Excellent temperature stability (no yellowing)

**Technical data:**

Colour: white

Consistency: fine powder

	Minimum	Maximum	Method
<b>Particle size*</b>			
Specified value:		99% < 19 µm	LV 5
Typical value:		50% < 6 µm	(ISO 13320)
Drop point:	143 °C	151 °C	LV 12 (DGF M-III 3)
Shelf life:	24 months (Stored in sealed original packing below 35 °C)		

*\* part of certificate of analysis*

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.  
EN Revision: October 2018