

CERETAN MF 5710

TECHNICAL INFORMATION

Chemical description: Spherical, micronized polyolefin wax modified with PTFE

Application: **Paints and coatings** e.g. can- and coil-, wood-, industrial and powder coatings

- Properties:**
- Very good scratch- and abrasion resistance
 - Good gloss and lubricating properties
 - Good temperature stability
 - Good solvent resistance
 - Higher PTFE content than CERETAN MXF 9510 D

- Advantages:**
- Spherical particle shape made by unique spraying technology
 - Specified maximum particle size (D99 value), narrow and uniform particle size distribution
 - Easy to disperse because of spherical particle shape

Technical data:

Colour:	white		
Consistency:	fine powder		
	Minimum	Maximum	Method
Particle size*			
Specified value:		99% < 10 µm	LV 5
Typical value:		50% < 4 µm	(ISO 13320)
Drop point _(wax) :	108 °C	118 °C	LV 12 (DGF M-III 3)
Melting point _(PTFE) :	320°C	340 °C	LV 1 (DIN EN ISO 3146)
Shelf life:	24 months (Stored in sealed original packing below 35 °C)		

** part of certificate of analysis*

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.
EN Revision: June 2016