

CERETAN MXF 9510 D

TECHNICAL INFORMATION

Chemical description: Spherical, micronized polyolefin wax, coated with PTFE

Application: **Printing inks**, especially sheetfed inks, flexo- and gravure inks
Paints and coatings, e.g. powder-, can-, coil-, auto-, industrial-, furniture- and parquet coatings

Properties:

- Excellent scratch and abrasion resistance
- Very good antiblocking
- Good gloss and slip properties
- Minimized dust properties compared to milled waxes

Advantages:

- The PTFE is homogeneously distributed on the surface of the wax
- Specified maximum particle size (D99 value), narrow and uniform particle size distribution
- PTFE concentration is reduced considerably by using „MXF“, which results in cost savings and quality improvements
- Easy to disperse because of spherical particle shape

Technical data:

Colour: white
Consistency: fine powder

	Minimum	Maximum	Method
Particle size*			
Specified value:		99% < 10 µm	LV 5
Typical value:		50% < 4 µm	(ISO 13320)
Drop point _(wax) :	108 °C	118 °C	LV 12 (DGF M-III 3)
Melting point _(PTFE) :	320°C	340 °C	LV 1 (DIN EN ISO 3146)
Shelf life:	24 months (Stored in sealed original packing below 35 °C)		

* part of certificate of analysis

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.
EN Revision: June 2016

MÜNZING Micro Technologies GmbH

Dr.-Bergius-Straße 16 - 24
D-06729 Elsteraue

Tel.: +49(0)3441/82910-22
Fax: +49(0)3441/82910-20
ceretan@munzing.com
www.munzing.com