

# CERETAN MX 9620

## TECHNICAL INFORMATION

<b>Chemical description:</b>	Spherical, micronized functional blend, based on Polyethylene and Amide wax		
<b>Application:</b>	<b>Paints and coatings, e.g. wood and powder coatings</b> <b>Masterbatch</b>		
<b>Properties:</b>	<ul style="list-style-type: none"> <li>• Very good scratch and abrasion resistance</li> <li>• Matting agent in wood coatings</li> <li>• Excellent slip</li> <li>• Good antiblocking and hot blocking</li> <li>• Very good degassing agent in powder coatings</li> </ul>		
<b>Advantages:</b>	<ul style="list-style-type: none"> <li>• Specific maximum particle size (D99-Value), narrow and uniform particle size distribution</li> <li>• Easily dispersible</li> </ul>		
<b>Technical data:</b>	Colour:	white	
	Consistency:	fine powder	
		<b>Minimum</b>	<b>Maximum</b>
		<b>Method</b>	
	<b>Particle size*</b>		
	Specified value:	99% < 20 µm	LV 5
	Typical value:	50% < 6 µm	(ISO 13320)
	Dropping point:	139 °C	149 °C
			LV 12 (DGF M-III 3)
	Shelf life:	24 months (stored in sealed original packing below 35 °C)	

*\* Part of certificate of analysis*