

CERETAN P 21

TECHNICAL INFORMATION

Chemical description: Nonpolar polypropylene wax

Application: High quality **pigment concentrates**
Plastics industry, e.g. polypropylene, PVC
 Modification of **hotmelt adhesive and coating hotmelts**
Melt adhesive based on EVA, APAO, PIB, SBS containing colophony- and hydrogenated hydro carbon resins

Properties:

- Low viscosity
- Easy dispersion and incorporation
- Lubricant
- Matting agent
- Improved abrasion resistance
- Dispersing agent

Technical data:	Colour:	white		
	Consistency:	powder		
		Minimum	Maximum	Method
	Drop point*:	156 °C	164 °C	LV 12 (DGF M-III 3)
	Viscosity (180°C):	100 mPas	200 mPas	LV 2 (DIN EN ISO 3104)
	Penetration:		0 mm*10 ⁻¹	LV 4 (DIN 51579)
	Acid value:		0 mg KOH/g	DIN EN ISO 2114
	Shelf life:	24 months (Stored in sealed original packing below 35 °C)		

** part of certificate of analysis*

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.
 EN Revision: June 2016