

# CERETAN<sup>®</sup> XT 23299

## TECHNICAL INFORMATION

<b>Product type</b>	Micronized wax, high molecular weight polyolefin based
<b>Application</b>	Texturing additive for coatings like wood, plastic and metal coating
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Texturing</li> <li>• Haptic effect</li> <li>• Scratch and abrasion resistance</li> <li>• Matting</li> <li>• Suited for anti-skid coatings</li> <li>• Narrow particle size distribution for a homogeneous surface texture</li> </ul>
<b>Processing Information</b>	According to the required effect, a dosage of 1-10% is added to the finished formulation.

<b>Technical Data</b>	<b>Colour</b>	white	
		<b>Minimum</b>	<b>Maximum</b>
	<b>Particle size*</b>		<b>Method</b>
	Specified value:		99% < 75µm
	Typical value:		50% < 25µm
	<b>Melting point</b>	160°C	170°C
			DSC (DIN EN ISO 11357-3)
	<b>Shelf life</b>	24 months (Stored in sealed original packing below 35°C)	

*\*part of certificate of analysis*

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Revision 03/2020

MÜNZING CHEMIE GmbH

Münzingstrasse 2  
D-74232 Abstatt

Tel.: +49(0) 7131/987-0  
Fax: +49(0) 7131/987-125  
[lubaprint@munzing.com](mailto:lubaprint@munzing.com)  
[www.munzing.com](http://www.munzing.com)