

CERETAN[®] XT 23399

TECHNICAL INFORMATION

Product type	Spherical micronized polyamide
Application	Texturing additive for coatings like wood, plastic and metal coating
Properties	<ul style="list-style-type: none"> • Texturing • Haptic effect • Very high scratch and abrasion resistance • Matting • Suited for high-temperature applications • Suited for anti-skid coatings • Very narrow particle size distribution for a homogeneous surface texture
Processing Information	According to the required effect, a dosage of 1-10% is added to the finished formulation.

Technical Data	Colour	white		
		Minimum	Maximum	Method
	Particle size*			
	Specified value:		99% < 35µm	Laser diffraction (ISO 13320)
	Typical value:		50% < 20µm	
	Melting point	170°C	180°C	DSC (DIN EN ISO 11357-3)
	Shelf life	24 months (Stored in sealed original packing below 35°C)		

*part of certificate of analysis

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Revision 03/2020

MÜNZING CHEMIE GmbH

Münzingstrasse 2
D-74232 Abstatt

Tel.: +49(0) 7131/987-0
Fax: +49(0) 7131/987-125
lubaprint@munzing.com
www.munzing.com