

CERETAN[®] XT 23499

TECHNICAL INFORMATION

Product type	Micronized wax, high molecular weight polyolefin based
Application	Texturing additive for coatings like wood, plastic and metal coating
Properties	<ul style="list-style-type: none"> • Texturing • Haptic effect • Scratch and abrasion resistance • Matting • Suited for anti-skid coatings • Narrow particle size distribution for a homogeneous surface texture
Processing Information	According to the required effect, a dosage of 1-10% is added to the finished formulation.

Technical Data	Colour	white	
		Minimum	Maximum
	Particle size*		Method
	Specified value:		99% < 40µm
	Typical value:		50% < 15µm
	Melting point	160°C	170°C
			DSC (DIN EN ISO 11357-3)
	Shelf life	24 months (Stored in sealed original packing below 35°C)	

**part of certificate of analysis*

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

Revision 03/2020

MÜNZING CHEMIE GmbH

Münzingstrasse 2
D-74232 Abstatt

Tel.: +49(0) 7131/987-0
Fax: +49(0) 7131/987-125
lubaprint@munzing.com
www.munzing.com